DISTRIBUTION	EW MEXICO OIL CONSERVATION COMMISSION	Form C-103 Supersedes Old C-102 and C-103
FILE	En mexico de conservation commission	Elffective 1-1-65
U.S.G.S.	1,127	
	How 7 I DOWN'67	5a. Indicate Type of Lease
	1104	State X Fee
OPERATOR		5. State Oil & Gas Lease No.
		К-1441
SUNDRY NOTICES	AND REPORTS ON WELLS L OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. -** (FORM C-101) FOR SUCH PROPOSALS.)	
USE "APPLICATION FOR PERMIT	-" (FORM C-101) FOR SUCH PROPOSALS.)	
OIL Y GAS		7. Unit Agreement Name
Name of Operator		
J. C. Williamson		8. Form or Lease Name
, Address of Operator		T. P. State
· · ·	d Tours	9, Well No.
726 Vaughn Bldg., Midland	u, lexas	
	S 1000	10. Field and Pool, or Wildcat
UNIT LETTER <u>R</u> 1980 FEET	FROM THE S LINE AND FEET	Wildcat
THE LINE, SECTION	TOWNSHIP 16 S RANGE 38 E	мрм. АННИНИИ
111111111111111111111111111111111111111	Elevation (Show whether DF, RT, GR, etc.)	12. County
	3715 DF	Lea
Check Appropriate	Box To Indicate Nature of Notice, Report or	Other Data
NOTICE OF INTENTION T		ENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	••••••
EMPORARILY ABANDON	COMMENCE DRILLING OPNS.	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB X	PLUG AND ABANDONMENT
	OTHER	
OTHER		
 Describe Proposed or Completed Operations (Clearl work) SEE RULE 1 103. 	y state all pertinent details, and give pertinent dates, inclu	ding estimated date of starting any propose
,		
	• · · · · · · · · · · · · · · · · · · ·	
Surface casing: Wel	1 spudded 4:40 p.m., 10/30/67	
Surface casing: Wel	1 spudded 4:40 p.m., 10/30/67	
Surface casing.	1 spudded 4:40 p.m., 10/30/67	
Total depth 412'		Shoo
Total depth 412' Ran 10 joints of 12 3/4" 32#	ST&C casing with Texas Pattern Guide	e Shoe.
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set		e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride.	ST&C casing with Texas Pattern Guide at 410' with ease 425 sacks Class C	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10	ST&C casing with Texas Pattern Guide at 410' with ease 425 sacks Class C	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement.	ST&C casing with Texas Pattern Guide at 410' with com 425 sacks Class C /31/67,	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement.	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50	ST&C casing with Texas Pattern Guide at 410' with etan 425 sacks Class C /31/67, 0#, held okay.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, O#, held okay. te.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, O#, held okay. te.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, O#, held okay. te.	e Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, 0#, held okay. te. d complete to the best of my knowledge and belief.	cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, O#, held okay. te.	2 Shoe. cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, 0#, held okay. te. d complete to the best of my knowledge and belief.	cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, 0#, held okay. te. d complete to the best of my knowledge and belief.	cement, 4%
Total depth 412' Ran 10 joints of 12 3/4" 32# Casing measured 411.90', set gel, 2% Calcium chloride. Plugged down at 10:50 a.m. 10 Circulated 40 sacks cement. Watied 24 hours, tested at 50 Now drilling at 4448' anhydri Thereby certify that the information above is true and	ST&C casing with Texas Pattern Guide at 410' with 425 sacks Class C /31/67, 0#, held okay. te. d complete to the best of my knowledge and belief.	cement, 4%