STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION

Form C-103

DISTRIBUTION		Revised 10-1-78	
SANTA FE	SANTA FE, NEW MEXICO 87501	5g. Indicate Type of Lease	
FILE		State Fee	
U.S.G.S.		5. State Oil & Gas Lease No.	
OPERATOR.		5. State Oil & Gas Estate inc.	
		mmmmmmy	
	SUNDRY NOTICES AND REPORTS ON WELLS		
(DO NOT USE THIS	FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name	
•		7. Olik Agreement 11-11-	
WELL S	OTHER- SWD	8. Farm or Lease Name	
. Name of Operator			
VERDE GRA	NDE INC.	AZTEC STATE	
. Address of Operator			
P.O.BOX 147 , LOVINGTON, N.M. 88260		1 10. Field and Pool, or Wildcat	
Location of Well			
	. 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	Whose shorted	
East	LINE, SECTION 18 TOWNSHIP 16S RANGE 37E NMPM.		
THE		12. County	
THITTINI.	15. Elevation (Show whether DF, RT, GR, etc.) 3837GL(est)	Lea	
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Oth	ier Data	
NO	TICE OF INTENTION TO: SUBSEQUENT	REPORT OF:	
	Y 1	L-1	
PERFORM REMEDIAL WORL	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	COMMENCE DRILLING OPHS.	PLUS AND ASANDONMENT	
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB		
AATE ON VELEN CHAPTER	OTHER	L	
erus			
	c Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed	
0 10 05.	pologed nacker and Degan remedial work.		
0 40 OF -	Arma againg look to be between 5.199' and 50/0'	1 000 -11	
3-17-85:		and Loo biletonen	
. ,	"C" cement. Circulated cement to surface with re	etrievable bridge	
	plug set at 5985'.		
3-19-85		ant had some	
to	to drilled out cement to 11.030' after finding cement had gone		
3-29-85	around the bridge plug. Circulated hole clean.	1 UPU nacker	
4-1-85	ran 344 joints tubing to 10,430' set Baker mode	ating to 500#	
•	after circulating 130 bbls. packer fluid and te	sting to 300%.	
4-2-85	returned well to injecting after acidizing with	h 1500 gal. 15%HCL.	
4-2-03	Total note to a first of the second of the s		
	•		
	·		
	the information above is true and complete to the best of my knowledge and belief.		
18. I hereby certify that	the information poor is		
0 /	05 (Pl Printer	DATE 7-10-86	
BISHER KALA	al. and the true		
		4000	
QRIGN	NAL SIGNED BY JERRY SEXTON	MAR 1 1 1986	
	DISTRICT I SUPERVISOR TITLE		

