## INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

# INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

#### Northwestern New Mexico

		20/01		a	T	Ojo Alamo	т	Penn "B"
Т. /	Anhy	2068	Т.	Canyon	1.			
т. 5	Salt		Τ.	Strawn	Т.	Kirtland-Fruitland	Т.	Penn. "C"
B. \$	Salt		Τ.	Atoka	Т.	Pictured Cliffs	Т.	Penn. "D"
		21201	Т.	Miss	T.	Cliff House	Т.	Leadville
	7 Rivers		Т.	Devonian	Т.	Menefee	T.	Madison
T. 0	Queen					Point Lookout		
Т.	Grayburg		Τ.	Montoya	Т.	Mancos	Т.	McCracken
т.	San Andres	4763'	Τ.	Simpson	T.	Gallup	T.	Ignacio Qtzte
т.	Glorieta	6356'				se Greenhorn		
	Paddock		Т.	Ellenburger	Т.	Dakota	т.	
Т.	Blinebry					Morrison		
T.	Tubb	7613'				Todilto		
т.	Drinkard					Entrada		
Т.	Abo	8257'	. <b>T</b> .	Bone Springs	Τ.	Wingate	Т.	
Т.	Wolfcamp_	9805'	. T.		Τ.	Chinle	Т.	
Т.	Penn.		. T.		Τ.	Permian	Т.	
тС	Cisco (Boug	gh C)	т.		Т.	Penn. "A"	T.	

### FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
Surfac 2068 3120 4763 6356 6425 7613 8257	3120 4763 6356 6425 7613 8257 9805	1052 1643 1593 69 1188 644 1548	Sand and red beds Anhydrite and salt Red shale, sand and anhy Dolomite and anhydrite Sand Dolomite, shale and anhy Sand and dolomite Red & green shale, anhy. and dolomite			rec. 60" 1 1:15' 60" 1 1:15' 10,8 GTS	57-820'/1:15" 5' mud SIP 460# ' FSIP 460# FP 46# ' FFP 46# 18-860'/1 hr. - 20 min. out 55 BO + 5 BSW
9805	10,903	1098	Limestone, dolomite, chert and shale			20" j 1 hr perio SIP 5 FP 1 Bott rec. oil,	out 55 BO + 5 BSW preflo FP 925-1154# ISIP 2198#, 1 hr flow od FP 1154-1927#, 2 hr 2153#, 2 hr flow period 950-2153#, 6 hr SIP 2176# om Hole Sampler 2100 cc, 100% wtr w/scum .1 of 1 cuft gas, sampler s. 600#