

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
TO THE DISTRICT ENGINEER
OF THE DISTRICT

Form No. 4
U.S. G.S. Bulletin No. 40-B-1424
U.S. DEPARTMENT OF THE INTERIOR

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such operations.)

1. LEASE OR SECTION AND SERIAL NO.
2. IF INDIAN, ALIQUOT OR TRACT NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WINGCASE

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, ET, GR, etc.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ *Injection*

2. NAME OF OPERATOR *Continental Oil Company*

3. ADDRESS OF OPERATOR *Box 460, Hobbs, New Mexico 88240*

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface *1150' FWL + 560' FEL, Section 23, T-17S, R-32E,
Sea County, New Mexico*

7. UNIT AGREEMENT NAME *MCC*

8. FARM OR LEASE NAME *MCC Unit*

9. WELL NO. *247*

10. FIELD AND POOL, OR WINGCASE *Mojave Pool*

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA *Sec. 23, T-17S, R-32E*

12. COUNTY OR PARISH *Sea* 13. STATE *N.M.*

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Spudded well 3:30 AM 7-30-68. Drilled 12 1/4" hole to 1035. Set 7 5/8" CD 24# H-40 surface casing at 1035. Cemented with 775 sacks Class H cement with 2% calcium chloride. Plug down at 2:15 PM 7-30-68. Cement circulated. WOC 12 hours. Tested with 800# for 30 minutes. Tested OK.

USGS-5 Partners-14 file

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

AUG 25 1968

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER