

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-5274

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator OLEN F. FEATHERSTONE	8. Farm or Lease Name Cabot State
3. Address of Operator 236 Petroleum Building, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 29 TOWNSHIP 15 S. RANGE 32 E. NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4326' GR.	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

### SURFACE

12-31-68 Spud.  
1-1-69 Total Depth 423' KB. Ran 411' (GR) new 12-3/4" 28# surface pipe and cemented with 450 sacks. Cement circulated. Plug down 2:45 P.M.  
1-2-69 WOC - 18 hours pressure tested 600# for 30 minutes with no pressure loss.

### INTERMEDIATE

1-8-69 Total Depth 4,105' in lime. Ran 4,093' (GR) new 8-5/8" 24# and 32# K55 and 28# H40 intermediate casing. Cemented 200 sacks Class C 50-50 pozmix followed by 200 sacks Class C cement. Plug down 2:36 P.M. Calculated top cement 2,373' from surface.  
1-9-69 9:00 A.M. pressure tested 1000# for 30 minutes with no pressure loss.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles W. Hicks TITLE General Manager DATE 1-9-69  
(Charles W. Hicks)  
APPROVED BY [Signature] TITLE [Signature] DATE [Signature]  
CONDITIONS OF APPROVAL, IF ANY: