

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-102
Supersedes Old
C-102 and C-103
Effective 1-1-65

AUG 11 10 35

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG 5242-1
7. Unit Agreement Name
8. Farm or Lease Name Featherstone-State
9. Well No. 1
10. Field and Pool, or Willcat Undesignated
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry
2. Name of Operator Cayman Corporation
3. Address of Operator 512 Midland Savings Building, Midland, Texas 79701
4. Location of Well UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 16S RANGE 34E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4052 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-5-69

Placed 25 sack cement plugs at:

11,412 - 11,512	6,025 - 6,125
10,600 - 10,700	4,540 - 4,640
8,360 - 8,460	3,240 - 3,340

7-25-69

Shot into and recovered 2174' of 8-5/8", 24# casing.
Placed cement plugs at:

2,135 - 2,185	25 sacks
1,650 - 1,700	25 sacks
200 - 240	25 sacks
Surface -	10 sacks
Installed marker	
9.5 lb. per gal. mud between all cement plugs	

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>John S. Goodrich</u>	TITLE <u>Engineer</u>	DATE <u>July 31, 1969</u>
APPROVED BY <u>John W. Runyan</u>	TITLE <u></u>	DATE <u>Aug 11 1970</u>
CONDITIONS OF APPROVAL, IF ANY:		