NO. OF COPIES RECEIVED		Forn Supe
DISTRIBUTION	- Country Coun	C-10 Effe
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	D1.0
FILE		5a. Indi
U.S.G.S.		Stat
LAND OFFICE		5. State
OPERATOR		
SUN 188 MET URE THIS PORM FOR	DRY NOTICES AND REPORTS ON WELLS PROPERTY OF PERMIT - 18 (FORM C-10 1) FOR SUCH PROPOSALS.)	
	CATION FOR PERMIT - (FORM S-TOT)	7. Unit
OIL GAS WELL	OTHER- Drilling	8, Form
2. Name of Operator	 -	St

m C-103 persedes Old

	 1	C-102 and C-103
DISTRIBUTION	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-85
ANTA FE	 	- -
ILE		5a. Indicate Type of Lease
.s.g.\$.		State X Fee.
AND OFFICE		5. State Oil & Gas Lease No.
PERATOR		в-2330
		muniformus -
SU	INDRY NOTICES AND REPORTS ON WELLS	
(BO NOT URE THIS FORM AND	PROBOTALS TO BRILL OR TO BE SEE OR PLUE BAR TO PROPOSALS.)	7. Unit Agreement Name
		,, ,
OIL GAS WELL	other. Drilling	8, Farm or Lease Name
Name of Operator		State B-2330
Jake L. Hamon		9. Well No.
Address of Operator		1
OOR Vaucha But	lding, Midland, Texas 79701	10. Field and Pool, or Wildcat
I eastion of Well		
_	1977.7 FEET PROM THE West LINE AND 560 FEET P	Undesignated
4 ==		
11 - - 16	SECTION 31 TOWNSHIP 16-S RANGE 36-E NE	мрм. (
THENorth LINE.	SECTION TOWNSHIP RANGE	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3932.5' GR.	Lea
	3932.3 GR.	Other Data
6. Ch	neck Appropriate Box To Indicate Nature of Notice, Report or	Office Data
NOTICE	OF INTENTION TO: SUBSEQU	ENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
	COMMENCE DRILLING OPNS.	PLUS AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS CASING TEST AND CEMENT JOB X	_
PULL OR ALTER CASING	OTHER	L
PULL OR ALTER CABING		L
0745	OTHER	LL
0745	OTHER	L
0745		L
other	eted Operations (Clearly state all pertinent details, and give pertinent dates, incl	L
7. Describe Proposed or Compl work) SEE RULE 1703.	eted Operations (Clearly state all pertinent details, and give pertinent dates, incl	L
7, Describe Proposed or Compl work) SEE RULE 1703.	eted Operations (Clearly state all pertinent details, and give pertinent dates, incl	L
7. Describe Proposed or Compl work) SEE RULE 1703.	eted Operations (Clearly state all pertinent details, and give pertinent dates, incl. P.M. 4-1-69. 2" hole to 432' and set the following casing.	L
7. Describe Proposed or Compl work) SEE RULE 103.	P.M. 4-1-69. 2" hole to 432' and set the following casing.	uding estimated date of starting any propos
OTHER 17. Describe Proposed or Compinary) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing.	uding estimated date of starting any proposed 1.09 435.52
OTHER 17. Describe Proposed or Complwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing	uding estimated date of starting any proposed 1.09 435.52 436.61
OTHER 17. Describe Proposed or Compinary) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B.	1.09 435.52 436.61 2.35
OTHER 17. Describe Proposed or Compinark) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from	1.09 435.52 436.61 2.35 434.26
OTHER (7. Describe Proposed or Complimork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top	1.09 435.52 436.61 2.35 434.26 of 12-3/4" 16.55
7. Describe Proposed or Compiwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top	1.09 435.52 436.61 2.35 434.26 of 12-3/4" 16.55
OTHER 17. Describe Proposed or Complwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin	1.09 435.52 436.61 2.35 434.26 of 12-3/4" 16.55 ag in hole 1.09 437.71
OTHER 17. Describe Proposed or Compinark) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin	1.09 435.52 436.61 2.35 434.26 16.55 19 in hole 2.3 CaCl. by
OTHER (7. Describe Proposed or Complimork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin	1.09 435.52 436.61 2.35 434.26 of 12-3/4" 16.55 ag in hole plus 2% CaCl. by
7. Describe Proposed or Compiwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin	1.09 435.52 436.61 2.35 434.26 16.55 19 in hole 2.3 CaCl. by
OTHER 17. Describe Proposed or Compinark) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	eted Operations (Clearly state all pertinent details, and give pertinent dates, inclinated and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Ci	1.09 435.52 436.61 2.35 434.26 ag in hole plus 2% CaCl. by Arculated cement.
7. Describe Proposed or Compiwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	eted Operations (Clearly state all pertinent details, and give pertinent dates, inclination) P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Cit	1.09 435.52 436.61 2.35 434.26 ag in hole plus 2% CaCl. by Arculated cement.
7. Describe Proposed or Compiwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	eted Operations (Clearly state all pertinent details, and give pertinent dates, inclination) P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Cit	1.09 435.52 436.61 2.35 434.26 ag in hole plus 2% CaCl. by Arculated cement.
7. Describe Proposed or Complwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	eted Operations (Clearly state all pertinent details, and give pertinent dates, inclinated and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Ci	1.09 435.52 436.61 2.35 434.26 of 12-3/4" 16.55 ag in hole plus 2% CaCl. by Arculated cement.
7. Describe Proposed or Complwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2	eted Operations (Clearly state all pertinent details, and give pertinent dates, inclination) P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Cit	1.09 435.52 436.61 2.35 434.26 of 12-3/4" 16.55 ag in hole plus 2% CaCl. by Arculated cement.
7. Describe Proposed or Compiwork) SEE RULE 1703. Spudded 10:00 Drilled 17-1/2 11 jts. 11 jts.	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Ci WOC for 24 hours and then tested casing for 30 600# pressure with no pressure leak.	1.09 435.52 436.61 2.35 434.26 ag in hole plus 2% CaCl. by Arculated cement.
7. Describe Proposed or Compiwork) see RULE 1703. Spudded 10:00 Drilled 17-1/2 11 jts. 11 jts.	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Ci WOC for 24 hours and then tested casing for 30 600# pressure with no pressure leak.	1.09 435.52 436.61 2.35 434.26 ag in hole plus 2% CaCl. by Arculated cement.
OTHER 17. Describe Proposed or Compinarly SEE RULE 1703. Spudded 10:00 Drilled 17-1/2 11 jts. 11 jts.	eted Operations (Clearly state all pertinent details, and give pertinent dates, inclination) P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Cit	1.09 435.52 436.61 2.35 434.26 a f 12-3/4" 16.55 ag in hole plus 2% CaCl. by lrculated cement. minutes with
7. Describe Proposed or Compiners) see Rule 103. Spudded 10:00 Drilled 17-1/2 11 jts. 11 jts.	P.M. 4-1-69. 2" hole to 432' and set the following casing. 12-3/4" Larkin Texas Pattern Shoe 12-3/4" 8V thd, ST&C, 34#, FWPS, R3 Casing Total Casing Out above K.B. Casing set from From K.B. to top 10 jts. of casin Cemented with 425 sacks of regular neat cement Halliburton. Plug down at 3:30 P.M. 4-2-69. Ci WOC for 24 hours and then tested casing for 30 600# pressure with no pressure leak.	1.09 435.52 436.61 2.35 434.26 ag in hole plus 2% CaCl. oy arculated cement.

	· · · · · · · · · · · · · · · · · · ·
	:
	The state of the s
	*
	- A Parkers I P. A Co. A Parkers I