

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

MAY 28 11 46 AM '69

Form C-103
Supersedes Old
C-103 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ **25** **AM '69**

5. State Oil & Gas Lease No.
K 5187

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Pennzoil United, Inc.	8. Farm or Lease Name State "C"
3. Address of Operator P. O. Drawer 1828 - Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER P , 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 16-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3813.8 GL	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-13-69 Spudded 17 1/2" hole at 2:30 P.M. - Drilled to 350'. - Ran 13 3/8" OD, 48# casing to 350'. Cemented w/180 sx Class "H" 6% gel plus 150 sx Class "H" 2% CaCl. - Plug down at 11:15 P.M. - Cement circulated.

5-14-69 After 18 hrs WOC, tested casing w/1,000# for 30 minutes - Tested O.K.

5-19-69 Drilled 11" hole to 4350'. Ran 8 5/8" OD, 24# & 32# casing to 4350'. - Cemented w/400 sx Class "H" 50/50 posmix 6% gel w/13.5# salt & 1/4# flocele per sack + 150 sx Class "C" w/8# salt & 1/4# flocele per sack. Plug down at 11:15 A.M. - Ran temperature survey. - Top cement at 2680'.

5-20-69 After 24 hours WOC, tested casing w/1,500# for 30 minutes - Tested O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. P. Goodrich, Jr. TITLE Drilling Superintendent DATE 5-27-69

APPROVED BY [Signature] TITLE [Signature] DATE JUN 4 1969

CONDITIONS OF APPROVAL, IF ANY:

