

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Clinton Oil Company		8. Farm or Lease Name Montieth "C" A.C.
3. Address of Operator c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N. M. 88240		9. Well No. 1
4. Location of Well UNIT LETTER _____, 1980 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 24, TOWNSHIP 16, RANGE 36 N.M.P.M.		10. Field and Pool, or Wildcat N.E. Lovington (Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 3846' D.F.		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Propose to set a CIBP w/20' cement on top at 11,000'.
2. Propose to set a 25 sx cement plug at 5 1/2 Casing stub at 10,000'.
3. Propose to set a 25 sx cement plug at top of Glorietta at 6224'.
4. Propose to set a 25 sx cement plug at 8-5/8 casing shoe at 4400'.
5. Propose to set a 25 sx cement plug at 8-5/8 casing stub at 1000'.
6. Propose to set a 25 sx cement plug at 13-3/8 casing shoe at 400'.
7. Propose to set a 10 sx cement plug at surface with marker.
8. Hole will be loaded with mud-laden fluids.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clement TITLE Agent DATE 6/20/71

APPROVED BY Leslie A. Clement TITLE OIL & GAS INSPECTOR DATE JUN 30 1971

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 22 1971

OIL CONSERVATION COMM.
HOBBS, N. M.