

COUNTY	LEA	FIELD	Wildcat	STATE	NM 30-025-23332
OPR	CAYMAN CORP.			MAP	
	1. Bell - State				
	Sec 2, T-16-S, R-33-E			CO-ORD	
	660' FNL, 660' FEL of Sec.				
	Spd 10-14-69		CLASS	EL 41982	
	Cmp 2-1-70	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
13 3/8" at 390' w/425 sx					
8 5/8" at 4350' w/400 sx					
7" at 4186' w/350 sx					
4 1/2" at 11,716' w/300 sx					
LOGS EL GR RA IND HC A					
		TD 12,702'			

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Moran Drlg. Co. PROP DEPTH 13,000' TYPE
DATE

	F.R. 10-21-69
	PD 13,000' (Morrow)
	Contractor - Moran Drlg. Co.
10-21-69	TD 4254'; Prep run 8 5/8" Casing
10-28-69	Drlg. 5604' 1m
11-3-69	Drlg. 7488' 1m
11-11-69	Drlg. 9860' 1m & sh
11-17-69	TD 10,677'; Lost Circulation
11-24-69	TD 10,677'; SI WOO
12-1-69	Drlg. 10,813' 1m, sh & cht
12-8-69	Drlg. 11,172' 1m, sh & cht
	DST 11,030-11,120', open 1 hr 15 min (1000' WB),
	Rec WB + 30' DM, 1 hr ISIP 736#, FP 735-475#,
	1 hr FSIP 523#
12-15-69	Drlg. 11,568' 1m & sd

LEA
CAYMAN CORP.

Wildcat
1 Bell - State

NM Sec 2, T16S, R33E
Page #2

12-15-69 Continued
DST (Seaman) 11,474-508', open 2 hrs 15 min
(950' WB), GTS 15 min @ 15 MCFGPD, Rec 100'
HO&GCWB + 850' O&GCWB + 250' GCO + 150' GCM,
1 hr ISIP 3815#, FP 428-514#, 2 hr FSIP 3624#

12-22-69 Drilg. 11,950' 1m, sh & cht
DST 11,657-678', open 2 hrs 30 min (1400' WB),
Rec 1400' GCWB + 10' oil + 30' GCM + 30' mud,
1 hr ISIP 3928#, FP 593-553#, 1 hr 30 min
FSIP 3789#

1-5-70 TD 12,590' 1m & sd; Cond Hole
DST 12,566-590', Pkrs failed

1-14-70 TD 12,702'; WOC
DST 12,559-590', Pkrs Failed

1-14-70 Continued
DST 12,530-590', Pkrs Failed (2500' WB)
DST (Atoka) 12,520-702', open 3 hrs 15 min
(2477' WB), Rec WB + 2433' GCM + 1600' GC
salt wtr, FP 1888-3048#, 2 hr FSIP 5612#

1-19-70 TD 12,702'; PBD 11,716'; WO Completion

2-2-70 TD 12,702'; PBD 11,716'; WO Completion

2-5-70 TD 12,702'; P&A (Holding For Tops)
Perf 11,488-496' w/2 SPF
Acid (11,488-496') 500 gals
Swbd 19 BNO + 18 BW in 3 hrs (11,488-496')
Acid (11,488-496') 2000 gals
Swbd 19 BF (90% wtr) in 9 hrs (11,488-496')
Perf 10,646-660' w/2 SPF
Acid (10,646-660') 500 gals
Swbd 30 B salt wtr in 1 hr (10,646-660')
Sqzd (10,646-660') w/135 sx.

2-5-70 Continued
Perf 10,645-655' w/2 SPF
Acid (10,645-655') 500 gals
Swbd 74 BW in 6 hrs (10,645-655')
-9-70 TD 12,702'; PLUGGED & ABANDONED
LOG TOPS: Anhydrite 1486', Yates 2708', Queen
3543', San Andres 4309', Glorieta 5715',
Tubb 7100', Abo 7860', Wolfcamp 9440', XX Marker
9730', Kemnitz 10,309', Cisco 10,632', Canyon
10,925', Strawn 11,904', Atoka 12,157'
3-12-70 COMPLETION REPORTED