

CSG & SX - TUBING				
13 3/8" at 415' w/350 sx				
8 5/8" at 4050' w/400 sx				
5 1/2" at 10,000' w/300 sx.				
LOGS EL GR RA IND HC A				
	TD 10,000'			

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

F.R. 10-28-69
PD 10,000' (Pennsylvanian)
Contractor - Cactus

11-10-69 Drlg. 100'
11-20-69 Drlg. 3800'
12-1-69 Drlg. 6901'
12-8-69 TD 9827' 1m & sh; Prep DST
12-15-69 TD 10,000'; Rng 5 1/2" Casing
DST 9796-9827', open 3 hrs 10 min, CTS 1 hr
42 min, Rec 200' O&GCM + 2800' salt wtr,
1 hr ISIP 2915#, FP 199-1557#, no FSIP
SP DST 9835-51', Pkrs Failed, Rec 280' HO&GCM +
985' GCM, 1 hr ISIP 2878#, FP 272#, no FSIP

12-22-69 TD 10,000'; WOG

IEA
SUN OIL CO.

Tulsa NM Sec 9, T13S, R32E
1 New Mexico "T" State Oil Com

Page #2

1-5-70 TD 10,000'; RU Pmp
Perf 9840-48' w/2 SPF
Acid (9840-48') 1000 gals
Swbd 53 BO + 80 BW in 10 hrs (9840-48')
Perf 9840-48' w/2 SPF
Acid (9840-48') 2500 gals
Swbd 33 BO + 25 BW in 6 hrs
1-12-70 TD 10,000'; WO Pmp
1-19-70 TD 10,000'; WO Pmp
1-27-70 TD 10,000'; TO Pmp
Tpd 16 BO + 20 BW in 24 hrs (9840-48')
2-2-70 TD 10,000'; TO Pmp
2-9-70 TD 10,000'; TO Pmp
Perf 9800-06'
Acid (9800-06') 2000 gals

2-9-70 Continued
Ppd 12 BLO + 8 BNO + 10 BW in 24 hrs (9800-48')
2-16-70 TD 10,000'; TO Pmp
2-24-70 TD 10,000'; Ppg load
Ppd 8 BO + 10 BW in 24 hrs (9800-48')
Acid (9800-48') 15,000 gals
3-2-70 TD 10,000'; TO Pmp
3-9-70 TD 10,000'; TO Pmp
Ppd 47 BO + 65 BW in 24 hrs
3-16-70 TD 10,000'; WO Potential
Ppd 17 BO + 20 BW in 24 hrs, GOR 2628
3-23-70 TD 10,000'; COMPLETE
LOC TOPS: Anhydrite 1504', Yates 2508', San
Andres 4117', Glorieta 5585', Tubb 6935',
Abo 7612', Wolfcamp 9110'
3-26-70 COMPLETION REPORTED