

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRY		7. Unit Agreement Name
2. Name of Operator <b>KING RESOURCES COMPANY</b>		8. Farm or Lease Name <b>Coates</b>
3. Address of Operator <b>300 Wall Towers West, Midland, Texas 79701</b>		9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>H</b> <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>660</b> FEET FROM THE <b>East</b> LINE, SECTION <b>14</b> TOWNSHIP <b>16-S</b> RANGE <b>36-E</b> NMPM.		10. Field and Pool, or Wildcat <b>Wildcat</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3867' GR</b>		12. County <b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-7-70 - Set 8-5/8" OD 24# & 32# K-55 casing @ 4850' KB. Cemented with 520 sxs Class "H", 50-50 Posmix, 6% Gel, 200 sxs Class "H" Neat. Ran Temperature Survey, found cement top @ 3000'.

6-8-70 - W.O.C. 24 hrs. Tested casing & BOP to 1000 psi. Held OK.

7-9-70 - T.D. 11,356' P&A as follows: 11,152 to 11,162 with 25 sxs, 10,423 to 10,523 with 25 sxs, 9385 to 9485 with 25 sxs, 6200 to 6300 with 25 sxs, 4830 to 4880 with 25 sxs.

7-21-70- Shot off & pulled 2991' of 8-5/8" OD casing. Plugged well as follows: 2950 to 2991 with 25 sxs, 325 to 375 with 25 sxs, 10 sxs at surface. Placed dry hole marker at well site.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *D.E. Dux* TITLE Drilling Foreman DATE 7-24-70

APPROVED BY *John W. Runyan* TITLE Geologist DATE MAY 1 1970

CONDITIONS OF APPROVAL, IF ANY: