

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
OG 5379	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Adobe Oil Company		Lovelady State
3. Address of Operator		9. Well No.
601 Wilkinson-Foster Bldg., Midland, Texas 79701		1-Y
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>south</u> LINE AND <u>660</u> FEET FROM THE <u>west</u> LINE, SECTION <u>32</u> TOWNSHIP <u>16-S</u> RANGE <u>33-E</u> N.M.P.M.		Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4221' Gr.		Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> testing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to P&A the Morrow section which was perforated from 13,471-13,474' and 13,529-13,543' and tested. We will set a cast iron bridge plug w/10' of cement on top at 13,300'. We will cut the 7" casing off where it is free and pull same. A 25 sx plug will be set at the top of the stub, 35 sx plug at the top of the Pennsylvanian, 25 sx plug at the top of Abo, 35 sx plug at the top of Glorieta, and a 35 sx plug at the base of 9-5/8" casing at 4630'. We will perforate the Queen section from approximately 4480-4490' and test it.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mr. H. R. Rye TITLE Vice President DATE 10/1/71

APPROVED BY John W. Runyan TITLE Geologist DATE OCT 4 1971

CONDITIONS OF APPROVAL, IF ANY: