

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>OG 5379</b>	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator <b>Adobe Oil Company</b>		8. Farm or Lease Name <b>Lovelady State</b>
3. Address of Operator <b>601 Wilkinson-Foster Bldg., Midland, Texas 79701</b>		9. Well No. <b>1-Y</b>
4. Location of Well UNIT LETTER <b>M</b> <b>660</b> FEET FROM THE <b>south</b> LINE AND <b>660</b> FEET FROM <b>west</b> <b>32</b> <b>16-S</b> <b>33-E</b> THE LINE, SECTION TOWNSHIP RANGE NMPM.		10. Field and Pool, or Wildcat <b>Wildcat</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4221' GL</b>		12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOB ☒  
OTHER ☐



17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 7:00 p.m. 11/12/70 with 17-1/2" hit. Drilled to 315' in red beds. Ran 10 jts 13-3/8" 48 & 54.5# casing to 315'. Cemented w/300 sxs class "C" w/2% CaCl. POB 5:30 a.m. 11/14/70. Circulated 45 sxs cement. Tested casing to 1000# for 30 minutes after WOC 24 hrs, pressure held o.k.

Drilled 12-1/4" hole to 4630' in lime. Ran 9-5/8" 36 & 40# casing to 4630'. Cemented w/200 sxs Trinity litevate plus 175 sxs class "C" cement w/8# salt per sx. POB 11/27/70. Tested casing to 1000# for 30 minutes after WOC 24 hrs, pressure held o.k.

Now drilling at 12,185' in lime.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	<b>M. D. Rogers</b>	TITLE <b>Vice President</b>	DATE <b>12/28/70</b>
APPROVED BY 	<b>SUPERVISOR DISTRICT</b>	TITLE	DATE <b>JAN 4 1971</b>
CONDITIONS OF APPROVAL, IF ANY:			