

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029405Cb)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Continental Oil Company
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, NM 88240
4. LOCATION OF WELL (Report location clearly and in accordance with applicable requirements.
See also space 17 below.)
At surface

RECEIVED
SEP 19 1973
U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

279

10. FIELD AND POOL, OR WILDCAT

Maj. G-SA Repress

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 19, T-175, R-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3942' est df

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Squeezing 6th zone perfs
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spotted 10' sand on top of bridge plug. Set cement
retainer at 3529' and pumped 250 gals NE acid
and 100 sacks Class C Cement to squeeze 6th zone
perfs. Drilled cement retainer at 3529' and
firm cement 3530'-3620'. Tested squeeze on
perfs w/ 1000 PSI for 15 minutes; held O.K.
Completed - 8-22-73

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Admin. Supervisor

DATE

9-18-73

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
SEP 20 1973
U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side