

P. O. BOX 1180 UNIT 1 STATES  
HOBBS, NEW MEXICO 88240  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR CONOCO INC.
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1345' FSL + 1345' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

## SUBSEQUENT REPORT OF:

- ☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

(other) SQUEEZE GRAYBURG, PERF SAN ANDRES

5. LEASE LC-029410 (A)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME MCA Unit
8. FARM OR LEASE NAME MCA Unit
9. WELL NO. 293
10. FIELD OR WILDCAT NAME Maljamar G/SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T17S, R32E
12. COUNTY OR PARISH LEA
13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU. Set RBP @ 3908'. PKR @ 3680'. Cmt Squeeze upper 6th Grayburg perfs 3844'-3895' w/ 24 BBLs of TFW, 5 BBLs 10# brine, 25 sxs class "c" & 25 sx thixotropic cmt. Flush w/ 24 BBLs of TFW. Rel pkr @ 3680'. DO cmt 3815'-3895'. DO to PBTD @ 4140'. Spot 2-1/2 BBLs 15% acid 3945'-4100'. Shot w/ 2 JSPF @ 4016'-4105'. Shot w/ 1 JSPF @ 3945'-3982'. Set RBP @ 4124' & pkr. @ 4075'. Acidize 9th zone 4092'-4105' w/ 19 BBLs of 15% acid. Flush w/ 25 BBLs TFW. Rel pkr. @ 4075' & RBP @ 4124'. Reset RBP @ 4075' & pkr @ 3910'. Squeezed perfs @ 3844'-3895' w/ 50 sxs class "c" cmt. Rel pkr @ 3910' & RBP @ 4075'. Ran prod. equip. Flowed 46 804262 BW on 7/31/84

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Und. Butterfield TITLE Administrative Supervisor DATE 10/15/84

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ ACCEPTED FOR RECORD \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: SWQ

OCT 22 1984

Carlsbad NEW MEXICO

\*See Instructions on Reverse Side