

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other Instru. 1 on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME MCA Unit
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME MCA Unit Bly 2
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, New Mexico 88240	9. WELL NO. 290
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1295' FNL & 1295' FWL - Unit Letter D	10. FIELD AND POOL, OR WILDCAT Maljama G-SA
14. PERMIT NO. 30-025-23798	11. SEC., T. R., M., OR BLK. AND SURVEY OR AREA 29-17S-32E
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. POOH w/pump & rods.
2. SI backside & squeeze perfs 3730' - 4040' down production tbg w/150 sxs cement. Open backside & circulate 200 sxs of class "C" cement w/2% CaCl₂ to 2300'.
3. Cut or backoff tbg to 2000'. POOH.
4. Set retained at 1900' & squeeze collapsed section at 2071'-2091' w/100 sxs class "C" cement w/2% CaCl₂.
5. Sting out of retained, circulate 9.5 ppq mud to surface.
6. Gradent head squeeze surface-production csq annulus w/175 sxs class "C" cement w/2% CaCl₂. If necessary, perf at 750' & circulate 175 sxs to surface. Set surface plug from 200' to surface.
7. Cut off wellhead & install P&H marker.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Administrative Supervisor

DATE January 12, 1988

This space for Federal or State office use)

APPROVED BY [Signature] TITLE

DATE 3 22 88

CONDITIONS OF APPROVAL, IF ANY:

*See instructions on Reverse Side

Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Callebad (6) Hondo (2) Citio (1) FPCO (1) File

RECEIVED

MAR 22 1988

CCD
HOBBY OFFICE