

UNIT STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLIC.  
(Other instructions on  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME MCA
2. NAME OF OPERATOR Continental oil Company	8. FARM OR LEASE NAME MCA Unit
3. ADDRESS OF OPERATOR Box 460 Hobbs New Mexico	9. WELL NO. 306
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1295' FNL and 2615' FEL of Sec 30	10. FIELD AND POOL, OR WILDCAT Meli G-5A Reprass
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3913' gr
	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec 30, T-17S, R-32E
	12. COUNTY OF PARISH Lea
	13. STATE N. Mex

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input checked="" type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) Commencement <input checked="" type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 12 1/4" hole on 3-27-72. Drld to 745'.  
Ran 8 5/8", 20 # casing and set at 745'. Cemented  
w/200 socks class C cement w/490 gel and 290  
Cach. Followed w/200 socks class C cement  
w/290 Cach. Cement circulated. WOC 24 hours.  
Tested casing for 30 minutes w/1000 psi. Held  
O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE

Admin Supervisor

DATE

4-17-72

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

APR 24 1972

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

USGSCS) MCA(3) File

\*See Instructions on Reverse Side

RECEIVED

APR 1 1972

OIL & CONSERVATION COMM.  
HOBBS, N. M.