

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator V-F Petroleum		8. Farm or Lease Name Allen
3. Address of Operator 1212 Vaughn Building, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>1650</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>1</u> TOWNSHIP <u>15S</u> RANGE <u>36E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3873.7 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Surface Casing String:

Ran 388.0 of 34# H-40 new casing set @ 400.0' KB. Cemented string with 400 sx Class H, w/2% CaCl. Circulated cement to surface. WOC a period of 12 hours. Tested casing to 500 psi for 30 minutes. No visible drop in pressure. Casing OK.

Intermediate Casing String:

Ran 4848' of 28#, J-55 and 32# J-55, 8-5/8" new casing, set at 4860' KB. Cemented w/400 sx. 2% CaCl. WOC a period of 12 hours. Tested casing to 1000 psi for 30 minutes. No visible drop in pressure. Casing OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief,

SIGNED J. M. Fuflinwider TITLE Co-owner DATE 4-7-72

J. M. Fuflinwider

Orig. Signed by

Joe D. Ramey TITLE

Dist. I, Supv.

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

DATE

APR 13 1972

RECEIVED

APR 12 1972

OIL CONSERVATION COMM.
HOBBS, N. M.