Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.

Use "APPLICATION FOR	R PERMIT—' for such proposals	
SUBMIT IN TRIPLICATE 1. Type of Weil Oni Gas Well Anjection 2. Name of Operator Conoco, Inc. 3. Address and Telephone No.		7. If Unit or CA, Agreement Designation
		8. Well Name and No Day T MCA Unit No. 311 9. API Well No. 3002524101 00
10 Desta Dr. Ste 100W, Midland, TX 79705 4 Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area Maljamar Grayburg SA
1295' FNL & 2615' FWL Sec. 26, T-17S, R-32E		11. County or Parish. State
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent Subsequent Report	Abandonment Recompletion	Change of Plans New Construction
Final Abandonment Notice	Plugging Back Casing Repair Altering Casing Other Casing Integrity Test	Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)
It is proposed to perform the for temporary abandonment:	aldepths for all markers and zones pertinent to this work.)* following operations in order to preport or performing casing integrity test. t 500 psi for 30 minutes. uid.	pare this injection well AREA TO THE SEVED THE SEVED
14. I hereby ceratry that the foregoing is true and street Signed (This peace for Federal of State office use) Approved by (ORIG SGD) IOF G, LARA Conditions of approval, if any:	Tide PETROLEUM ENGINEER	tor Date 4/21/93 Date 5//3/93

MINIMUM REQUIREMENTS FOR CASING INTEGRITY TESTING OF WELLS ON FEDERAL LEASES IN THE CARLSBAD RESOURCE AREA

1. Contact the appropriate BLM office at least 24 hours prior to the scheduled test.

NOTE: A BLM tecnician must be present to witness all casing integrity tests.

- 2. A retrievable bridge plug or packer shall be set a maximum of fifty (50) feet above any open perforations.
- 3. All downhole production equipment (tubing, rods, etc.) must be removed from the casing if they are not isolated by a packer.
- 4. The casing must be filled with fluid and pressure tested to 500 PSI. Further, the casing must be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off (ie., down to 450 PSI).
- 5. Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment status for a period of 12 months provided that the operator submits a subsequent Sundry Notice requesting TA approval, and attaches a copy of The pressure test chart for the tested well.