

COUNTY LEA FIELD Maljamar STATE NM 30-025-24121 ✓
 OPR CONTINENTAL OIL CO. MAP
 313 MCA Unit
 Sec 25, T-17-S, R-32-E
 450' FNL, 1980' FWL of Sec CO-ORD
 Spd 6-19-72
 Cmp 7-27-72 CLASS EL 4032 ~~2~~
 CSG & SX TUBING
 8 5/8" at 1100' w/550 sx
 5 1/2" at 4350' w/300 sx
 LOGS EL GR RA IND HC A
 TD 4350'
 IP (Grayburg-San Andres) Perfs 4037-4308' P 25 BOPD + 445 BW.
 Pot based on 24 hr test. GOR NR; Grav 37.5

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus PROP DEPTH 4350' TYPE RT
 DATE

F.R. 5-8-72; Opr's Elev. 4024' GL
 PD 4350' RT (Grayburg-San Andres)
 Contractor - Cactus
 6-26-72 Drig. 3922' 1m
 7-10-72 TD 4350'; Flwg 1d
 Cored 4002-62', rec 60', no descr
 Cored 4062-4107', rec 45', no descr
 Cored 4107-66', rec 59', no descr
 Cored 4166-4228', rec 62', no descr
 Cored 4228-90', rec 62', no descr
 Perf @ 4204', 4213', 4218', 4222', 4258', 4270',
 4285', 4292', 4308' w/1 SPI
 Perf @ 4037', 4080', 4083', 4086', 4117', 4120',
 4125' w/1 SPI
 Acid (4204-4308') 10,200 gals

LEA
CONTINENTAL OIL CO.

Maljamar
313 MCA Unit

NM Sec 25, T17S,R32E
Page #2

7-17-72 TD 4350'; WOC
Vis Sqzd 4080-86' w/300 sx
Vis Sqzd 4037-4123' w/100 sx
7-24-72 TD 4350'; Tstg
Perf @ 4117', 4120', 4123' w/2 SPF
Acid (4117-23') 2000 gals
Frac (4117-23') 20,000 gals jelled wtr + 40,000# sd
Flwg @ 300 BWPD + trace oil thru 1/2" chk (4117-
23')
7-31-72 TD 4350'; Tstg
Ppd 11 BO + 257 BW in 70 hrs (4037-4308')
8-7-72 TD 4350'; WO Pot
Ppd 25 BO + 445 BW in 24 hrs, Grav 37.5
8-14-72 TD 4350'; COMPLETE
8-19-72 COMPLETION REPORTED
