

COUNTY LEA FIELD Shoe Bar, E. STATE NM 30-025-24151

OPR HANKS, ROGER C. MAP

2 Graham

Sec 29, T-16-S, R-36-E CO-ORD

1980' FSL, 660' FWL of Sec

Spd 6-28-72

Cmp 8-27-72 CLASS EL

|  | FORMATION | DATUM | FORMATION | DATUM |
|--|-----------|-------|-----------|-------|
|--|-----------|-------|-----------|-------|

CSG & SX - TUBING

13 3/8" at 464' w/450 sx

8 5/8" at 4270' w/350 sx

5 1/2" at 13,002' w/400 sx

LOGS EL GR RA IND HC A

TD 13,010'

IP (Devonian) Perfs & OH 12,992-13,010' F 720 BOPD + 10 BLW.

Pot based on 24 hr test thru 1/2" chk. GOR 555; Grav NR; CP

Pkr; TP 360#

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sharp PROP DEPTH 13,200 TYPE RT

DATE

F.R. 6-5-72; Opr's Elev. 3927' GL

PD 13,200' RT (Devonian)

Contractor - Sharp

7-11-72 Drlg. 6240'

7-17-72 Drlg. 8420' lm & sh

7-25-72 Drlg. 10,825' lm & sh

8-1-72 Drlg. 12,175' lm & sh

8-7-72 Drlg. 12,945' sh

8-15-72 TD 13,010'; WOC

DST 12,985-13,010'; Pkr Failed

DST 12,978-13,010', open 1 hr 30 mins (3000' WB),

GTS in 2 hrs 38 mins, rec 822' oil + 3000' GCWB +

60' GCM, 1 hr ISIP 4763#, FP 1420-1677#, 2 hr

FSIP 4336#, HP 6386-6344#

9-11-72 TD 13,010'; Tight

LEA  
HANKS, ROGER C.

Shoe Bar, E.  
2 Graham

NM Sec 29, T16S, R36E  
Page #2

9-18-72 TD 13,010'; COMPLETE  
Perf 12,992-13,000' w/4 SPF  
Acid (12,992-13,010') 250 gals  
LOG TOP: Devonian 12,978'  
Well Drilled Tight  
9-23-72 COMPLETION REPORTED