## N. M. OIL CONS. COMMISSION

Form 9-331 Dec. 1973

P. O. BOX 1980

UNITED STATES HODBS, NEW MEXICO 88240

Form Approved. Budget Bureau No. 42-R1424

## DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

5. LEASE LC-058698/91 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 9. WELL NO. 10. FIELD OR WILDCAT NAME Maljamar (G/SA 11. SEC., T., R., M., OR BLK. AND SURVEY OR

gas well other NAME OF OPERATOR 3. APPRESS OF PEROTOS N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

Jec, 26, T175, R32E

12. COUNTY OR PARISH 13. STATE

AT SURFACE: 1880' FNL 9 560' FWL

AT TOP PROD. INTERVAL: ~ AT TOTAL DEPTH: V

REPORT, OR OTHER DATA

14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE

SUBSEQUENT REPORT OF:

Report results of multiple completion or zone change on Form 9-330.)

CHANGE ZONES ABANDON\* (other) Cement squeeze AUG 2 6 1982

DIL & GAS MINERALS MGMT. SERVICE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS CHEEN MEXICO pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

There is a waterflow in the production-surface casing annulus

Pump 200 St class "c" cement w/ 290 Ca C/2.

Shutin for 3 days.

Open casings value and report results.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	<del>-</del>
SIGNED Was Q. Bulley Just TITLE Administrative Supervisor DA	TE 8-24-82
(This space for Federal or State office use)	
APPROVED BY	DATE
AUG 3 4 19g	
FOR	
JAMES A. OILTHAN DISTRICT SURERVISOR*See Instructions on Reverse Side	