

COPY TO G. E. E.

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☒ gas well ☐ other
2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1245' FSL, 50' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: SAME
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐

5. LEASE
LC-029509 (6)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
M.C.A. Unit
8. FARM OR LEASE NAME
M.C.A. Unit
9. WELL NO.
326
10. FIELD OR WILDCAT NAME
MALJ. G-5A
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 21, T. 17 S, R. 32 E
12. COUNTY OR PARISH LEA 13. STATE N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4038' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

AUG 23 1978

U. S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and completion dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBJECT WELL ACIDIZED AS FOLLOWS:

- RIG UP, pull prod. eqpt. (7-6-78)
- SET RBP @ 4010', spot 300 gals HCL-NE acid, flush w/ 23 bbls FW.
- SET PKR @ 3934', pumped 10 bbls FW. dn. tbg.
- pmpd 1500 gals 15% HCL-NE, flush w/ 23 bbls FW.
- moved RBP & set @ 3904', PKR @ 3779', press. upon CSG TO 300 psi
- pmpd 4 bbls FW, started w/ 1200 gals 15% HCL-NE acid
- flushed w/ 24 bbls FW.
- pull acidizing eqpt, run prod. eqpt., place well on prod.


Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. A. Butterfield TITLE Admin. Supv DATE 8-21-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:



*See Instructions on Reverse Side

4565 [5] MCA [4] FILE