

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUBMIT IN T
(Other Instruc
verse side)
88240

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME <i>MCA Unit</i>
2. NAME OF OPERATOR <i>Conoco Inc.</i>	8. FARM OR LEASE NAME <i>MCA Unit Bty 3</i>
3. ADDRESS OF OPERATOR <i>P.O. Box 460 - Hobbs, New Mexico 88240</i>	9. WELL NO. <i>332</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>25' FSL & 1345' FEL - Unit Letter O</i>	10. FIELD AND POOL, OR WILDCAT <i>Maljamae C-SA</i>
14. PERMIT NO. <i>30-025-24349</i>	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
	12. COUNTY OR PARISH <i>Lea</i>
	13. STATE <i>NM</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <i>Repair Surface Waterflow</i> ☒	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. Tag fill at 4174'. Clean out to 4168'. POOH w/ Hbg & scraper. Set RBP at 1610'. Spot 2 sxs sand on top. Pressure test to 500 psi. Shot 2 holes at 850'. Rmpd 25 BW down 8 7/8" & 5 1/2" to get circulation. Pump 10 bbl caustic water, 24 bbls H₂O-check, 225 sxs class "H" cement w/ 2% CaCl₂ thru 5 1/2" & circulate out of 8 7/8", close 8 7/8" cement come out of ground. Release p.k. Drill out cement 780'-850'. Pressure test to 800 psi. Scrape to 375'. POOH. Fish RBP. Tag at 4174'. Pump 130 BW down csq. Place well on production.

SJS

18. I hereby certify that the foregoing is true and correct

SIGNED *DF FINNEY*

TITLE *Administrative Supervisor*

DATE *November 24, 1987*

For space for (General or State office use)

APPROVAL OF
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See instructions on Reverse Side

Under the Espionage Laws, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BLM-Carlsbad (6) Hondo (2) Artesia (1) FPCO (1) File