

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other PLA
2. NAME OF OPERATOR
Conoco Inc.
3. ADDRESS OF OPERATOR
P.O. Box 460 Hobbs N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1225' FNL & 1295' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) Re-enter & PLA

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☒

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE

LC-061841

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MCA

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

342

10. FIELD OR WILDCAT NAME

Maljamar G-5A

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-17S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3975' GR

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 2-1-80. Drilled out 30' cmt. @ surface.Drilled on cmt. plug from 900' to 930'. Drill retainer @ 2125'-2155'.Spot 20-sack class "C" cmt. plug from 2150' to 2000'. Spot 15 sk.Class "C" cmt. from 1150' to 1000'. Perf. @ 900' & again @ 870' w/ 2JSPF. Could not pmp. into perfs. Perf @ 500' w/ 2 JSPF. Able to estab.circ. Pumped 160 sk. class "C" cmt. w/ additives dn. 5 1/2" csg. Circ.40 sk. cmt. to pit from csg.-csg. annulus. Erect dry hole marke& clean location 2/7/80
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butler TITLE Admin. Supervisor DATE 2/8/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

USGS-5MCA-4FILE

NOT
RECORDED

OIL CONSERVATION DIV.

FEB 19 '80

RECEIVED