

CONTR 020105 OPRS ELEV PD 4600 TYPE RT

W.R. 10-1-73
(Grayburg-San Andres)
11-26-73 Drlg 2800' anhy & salt
12-4-73 Drlg 4100' anhy & lm
12-11-73 TD 4552'; Prep Run 4 1/2" csg
 Cored 4240-4300', rec 60', no descr
 Cored 4300-4351', rec 51', no descr
 Cored 4351-4370', rec 19', no descr
 Cored 4370-4431', rec 61', no descr
 Cored 4431-4491', rec 60', no descr
 Cored 4491-4552', rec 61', no descr
12-18-73 TD 4552'; PBD 4512'; Swbg
 Pore 4310-4428' w/80 shots (overall)
 Acid (4310-4428') 2000 gals (15%)
 Swbg 16 BAW + 69 B salt wtr in 9 hrs (4310-4428')

LEA
PHILLIPS PET. CO.

Maljamar
17 Leamax
Sec 16, T17S, R33E

NM
Page #2

1-2-74
TD 4552'; PBD 4410'; RU Pmp
Perf 4311-4393' w/ 60 shots (overall)
Acid (4311-4393') 1500 gals
Swbd 4 BO + 4 BAW (4311-4393')
Frac (4311-93') 20,000 gals ref oil + 30,000# sd
1-8-74 TD 4552'; PBD 4410'; TO Pmp
1-14-74 Ppd 100 BLO in 24 hrs (4311-4393')
TD 4552'; PBD 4410'; TO Pmp
1-21-74 Ppd 50 BNO in 24 hrs (4311-93')
1-26-73 TD 4552'; PBD 4410'; COMPLETE
COMPLETION REPORTED