NO. OF COPIES RECEIVED		Para Garage
DISTRIBUTION		Form C-103 Supersedes Old
SANTAFE	NEW MEXICO OIL CONSERV. TION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE		Tuective 1-1-02
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State Fee X
OPERATOR		5. State Oil & Gas Lease No.
CLIX	IDDV NOTICES AND DESCRIPTION	
OD NOT USE THIS FORM FOR	NDRY NOTICES AND REPORTS ON WELLS R PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1.	TOTAL FOR PERMIT 2" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
OIL GAS WELL WELL	OTHER-	7. Ollit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Hilliard Oil & Ga	s, Inc.	Goodrich
3. Address of Operator		9. Well No.
906 Building of th	e Southwest, Midland, Texas 79701	1
4. Location of well		10. Field and Pool, or Wildcat
UNIT LETTER	1980 FEET FROM THE North LINE AND 1980 FEET FRO	Wildcat
West	11 18 0 08 00	
THE WEST LINE, SE	ECTION 11 TOWNSHIP 15-S RANGE 35-E NMPI	
	15. Elevation (Show whether DF, RT, GR, etc.)	
		12. County
16.		Lea
NOTICE OF	ck Appropriate Box To Indicate Nature of Notice, Report or O	
7,01,02,01	SUBSEQUEN	IT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	<u></u>
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ABANDONMENT
	OTHER	Γ-
OTHER		
17 Describe Proposed or Complete	Convertions (Clearly state all and all all and all all and all all all and all all all all all all all all all al	
work) SEE RULE 1103.	d Operations (Clearly state all pertinent details, and give pertinent dates, includin	g estimated date of starting any proposed
Plugging commendate Set Plugs of Set Plugs o	n plugged and abandoned as follows:  ced on 11-30-73:  as follows:  ug - 35 sx cement - 14120 to 14220  ug - 35 sx cement - 10550 to 10650  ug - 35 sx cement - 9750 to 9850  ug - 35 sx cement - 7975 to 8075  ug - 35 sx cement - 6100 to 6200  ug - 35 sx cement - 4650 to 4750 - 1/2 in, 1/3  5/8" csg @ 1305' (base of 8-5/8" @ 4698')  ug - 50 sx cement - 1205 to 1305  ug - 50 sx cement - 305 to 450 - 1/2 in, 1/3  ug - 10 sx cement - Surface to 20'  ry hole marker.  ompleted on 12-1-73. Pits & location will be clean	2 out of 13-3/8" csg.
possible	ion above is true and complete to the best of my knowledge and belief.	caneu up as soon as
SIGNED MAINT	Manager of Operations	12-13-73
$\mathcal{O}U$ .	K. Geologia	
APPROVED BY MA W.	Muyan TITLE	DATE
CONDITIONS OF APPROVAL, IF A	NY:	-