

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☒ GAS WELL ☐ OTHER- Re-Entry

Name of Operator

Manzano Oil Corporation

Address of Operator

Box 571, Roswell, New Mexico 88201

Location of Well

UNIT LETTER P, 555 FEET FROM THE South LINE AND 765 FEET FROM
THE East LINE, SECTION 12 TOWNSHIP 16S RANGE 35E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Gantt

9. Well No.

#1

10. Field and Pool, or Wildcat
Undesignated
Shoebar North

11. Elevation (Show whether DF, RT, GR, etc.)

3960' GR

12. County
Lea

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

☐

☐

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

☐

☐

☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-20-84 Moved in Rotary and rigged up. Started drilling surface cement plug at 10:00PM.
8-23-84 2515' tagged top of 9 5/8" casing.
8-24-84 Ran 60 jts. (2543') 9 5/8" 36# ST&C casing and tie into top of 9 5/8" stub previously cemented to 4160'. Cemented with 400 sacks Halliburton light and 200 sacks Class "C" with 2% CaCl₂. Plug down at 11:45 AM 8-24-84. Circulated 50 sacks cements. WOC.
8-25-84 Nipple up BOP and tested to 1000# for 30 minutes - held ok. Went in with 8 1/2" bit hit tight spot at 2515'. Trip out and back in with full gauged tapered mill and cleaned up tight spot. Trip out and backin with 8 1/2" bit and drilling cement.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CHECKED Chenfer W. Hicks

TITLE Vice-PRES.

DATE 9/5/84

ORIGINAL SIGNED BY JERRY SEKTON
DISTRICT 1 SUPERVISOR

TITLE

DATE

SEP 10 1984

CONDITIONS OF APPROVAL, IF ANY:

