

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn 11,270
B. Salt	T. Atoka 11,395
T. Yates 3112	T. Miss 11,892
T. 7 Rivers	T. Devonian
T. Queen 3975	T. Silurian
T. Grayburg	T. Montoya
T. San Andres 4720	T. Simpson
T. Glorieta 6240	T. McKee
T. Paddock	T. Ellenburger
T. Blinebry	T. Gr. Wash
T. Tubb 7456	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo 8158	T. Rustler 1894
T. Wolfcamp 9523	T. Tansil 2984
T. Penn	T. 3 Bros. 10262
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0	1894	1894	Surface sands & Redbed
1894	2984	1090	Andydrite & Salt
2984	4163	1179	Andydrite & Gyp
4163	6240	2077	Dolomite & Anhydrite
6240	7456	1216	Lime & Shale
7456	8158	702	Lime
8158	10,262	2104	Lime & Shale
10,262	12,270	1008	Lime & Shale – 3 Bros.
11,270	11,395	125	Lime & Shale – Strawn
11,395	11,892	497	Sn & Shale & Lime – Atoka
11,892	12,012	120	Shale

From	To	Thickness In Feet	Lithology

