NEW MEXICO OIL CONSERVATION COMMISSION    State   Stat	TRIBUTION	NEW MEXICO OIL CONSERVATION COMMISSION		Form C-103 Supersedes Old C-102 and C-103
Supply Notices and Reports on Wells   Supply Notices and Reports of Supply N				
SUNDRY NOTICES AND REPORTS ON WELLS  SUBJECT OF SUNDRY NOTICES AND REPORTS ON WELLS  SUBJECT ON THE THIRD SUNDRY NOTICES AND REPORTS ON WELLS  SUBJECT ON THE SUNDRY NOTICES AND REPORTS ON WELLS  SUBJECT ON THE SUBJECT ON SUNDRY NOTICES AND REPORT OF SUNDRY NOTICES O				
SUNDRY NOTICES AND REPORTS ON WELLS    Control   Control				
The state of Special Special State of Special Special Special State of Special Specia				K - 5953
Special Complete Complete Co.  S. Address of Coperator  P. O. Box 2009, Amarillo, Texas 79105  S. Licenses of Coperator  P. O. Box 2009, Amarillo, Texas 79105  S. Licenses of Coperator  K. 1980		NOTICES AND REPORTS ( OSALS TO DRILL OR TO DEEPEN OR PLU N FOR PERMIT - " (FORM C-101) FOR	N WELLS G BACK TO A DIFFERENT RESERVOIR. SUCH PROPOSALS.)	7. Unit Agraement Name
Monsanto State  3. Activations of Well  P. O. Box 2009, Amarillo, Texas 79105  4. Location of Well  OUT CETTER  K. 1980 rect proof the South  OUT CETTER  West Line, ACCITON 14 TOWNSHIP 165 RANGE 35E AMARIA  THE West Line, ACCITON 14 TOWNSHIP 165 RANGE 35E AMARIA  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  PULIC AND ARASCON 15 TOWNSHIP 165 RANGE OF THE PULIC RESIDENT REPORT OF:  CHARLE FLARE CASHIE  OTHER		OTHER-		7. Our Agreement Name
3. Address of Operators P. O. Box 2009, Amarillo, Texas 79105 4. Location of Well A. Location of Well List and 1980 FETT FROM THE SOUTH LIST AND 1980 FETT FROM THE SOUTH LIST AND 1980 FETT FROM THE SOUTH LIST AND 1980  THE West List, Section 14 Township 16S RANGE 35E Number 12 Country 15. Elevation (Show whether DF, RT, GR, etc.)  16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  PLUS AND ABANDON COUNTRY AND THE COUNTRY AND ABANDON COUNTRY AND ABANDO	2. Name of Operator	And the second s		
P. O. Box 2009, Amarillo, Texas 79105  4. Location of Well  1980  ***Extreme The South Live And 1980  ***Extreme The South Live And 1980  ***The West Line, SECTION 14 TOWNSHIP 16S NAMEE 35E NUMBER 12. County Lea 3980' GR  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF:  ***PRICE AND ARABDON**  ***OWNERS CONNECTED FOR INTENTION TO:**  ***PRICE OF INTENTION TO:**  ***PRICE AND ARABDON**  ***OFFICE OF INTENTION TO:**  ***PRICE OF INTENTION TO:**  ***OFFICE OF INTENT				
Undesignated Morrow  West VINE, SECTION 14 TOWNSHIP 16S SANGE 35E NUMBER  15. Elevation (Show whether DF, RT, GR, etc.)  3980' GR  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF:  NOTICE OF INTENTION TO:  PRAYER MEMBRIAL WORK  THUS AND ABANDON  THE TABLE CASING  OTHER  17. DESCRIBE TOWNSHIP A COMMERTAND OF THE TABLE CASING  THUS AND ABANDON  THE TABLE CASING  OTHER  17. DESCRIBE TOWNSHIP A COMMERTAND OF THE TABLE CASING  THUS AND ABANDON  THE TABLE CASING  OTHER  17. DESCRIBE TOWNSHIP A COMMERTAND OF THE TABLE CASING  THUS AND ABANDON  THE TABLE CASING  OTHER  17. DESCRIBE TOWNSHIP A COMMERTAND OF THE TABLE CASING  THUS AND ABANDON  THE TABLE CASING  OTHER  17. DESCRIBE TOWNSHIP A COMMERTAND OF THE TABLE CASING  THUS AND ABANDON  THE TABLE CASING  OTHER  COMMERTAND OF THE TABLE CASING  THUS AND ABANDON  THE TABLE CASING  THUS AND ABANDON  ALTER CASING  CHAMEE TABLE  COMMERCE TABLE	·	rillo, Texas 79105		1
West UNE, SECTION 14 16S NAME 35E NAME.    12 COURTY   16	·· —	1000		•
15. Elevation (Show whether DF, RT, GR, etc.)  3980' GR  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  PERFORM MEMIDIAL WORK  TOWNGRAFILY ARABDON  PULL OR ALTER CASING  OTHER  17. DESCRIPTION PROCESSED OPERATION (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed unwell set will be 108.  Spudded well 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Clas H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1'Howco guide shoe  1325' 9 5/8" 36# K-55 ST&C (60 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18, I hereby certify that the information above is true and complete to the best of my knowledge and belief.  Title Production Engr.  Approved by  Approved b	UNIT LETTER K	1980 FEET FROM THE Sout	h LINE AND 1980 FEET	Glidesignated Mofrow
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  SUBSEQUENT REPOR	THE West LINE, SECTION	14	6S RANGE 35E N	MPM.
NOTICE OF INTENTION TO:    PERFORM REMEDIAL WORK			er DF, RT, GR, etc.)	
TEMPORABLEY ABANDON PULL OR ALTER CASING  OTHER  17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) see Rule 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Clas H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe  1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18. Thereby certify that the information above is true and complete to the best of my knowledge and belief.  The production Engr.  PAGE PLANE OF THE CASING TEST AND CEMENT JAB APPROVED BY  APP				
TEMPORABILY ABANDON  FULL OR ALTER CASING  OTHER  17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) see RULE 1103.  Spudded well 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Clas H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe  1325' 9 5/8" 36# K-55 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.  Production Engr.  Production Engr.  PATE NOV 2			¬	ALTERIUS SAGING
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) see MULE 1703.  Spudded well 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Class H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe 1325' 9 5/8" 36# S-80 ST&C (36 jts) 2855' 9 5/8" 36# K-55 ST&C (60 jts) 4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.  **INNEL Production Engr.**  **OATE 11-20-74*  **NOV { **INNEL Production Engr.**  **OATE 11-20-74*  **NOV { **INNEL Production Engr.**  **OATE 11-20-74*  **NOV { **APPROVED BY TILLE **PATE PRODUCTION TO STATE 11-20-74*  **NOV { **APPROVED BY TILLE **PATE PRODUCTION TO STATE 11-20-74*  **NOV { **APPROVED BY TILLE **PATE PRODUCTION TO STATE 11-20-74*  **NOV { **APPROVED BY TILLE **PATE PRODUCTION TO STATE 11-20-74*  **NOV { **APPROVED BY TILLE **PATE PRODUCTION TO STATE 11-20-74*  **APPROVED BY TILLE **PATE PRODUCTION TO STATE 11-20-74*  **APPROVED BY TILLE PRODUCTION TO STATE 11-20-74*  **APPROVED B	$\vdash$	PLUG AND ABANDON [		<del> </del>
17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) see RULE 1103.  Spudded well 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Clas H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe  1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.  **TITLE** Production Engr.  **DATE** **ITILE** **Production Engr.** **DATE** **ITILE** **PODUCTION Engr.** **DATE** **ITILE** **PODUCTION Engr.** **DATE** **PODUCTION Engr.** **PODUCTION Engr.*		CHANGE PLANS	CASING TEST AND CEMENT JQB	
17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SER RULE 103.  Spudded well 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Class H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe  1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.  Production Engr.  OATE 11-20-74		[-	OTHER	
Spudded well 11:00 am 11-10-74. Drilled to 360'. Ran 12 jts of 13 3/8" 48# H-40 casing and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Clas H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe 1325' 9 5/8" 36# K-55 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.				
and set @ 358' RKB. Centralizers on first and third collars. Cemented with 375 sxs Clas H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe 1325' 9 5/8" 36# S-80 ST&C (36 jts) 2855' 9 5/8" 36# K-55 ST&C (60 jts) 4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.		rations (Clearly state all pertinent o	letails, and give pertinent dates, inclu	ding estimated date of starting any proposed
H w/2% cc. Plug down @ 7:45 PM on 11-10-74. Cement circulated. WOC 24 hrs. Tested casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe  1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs  Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.				
casing to 750 psi - 30 min, OK. Drilled to 4168'. Ran 9 5/8" casing as follows:  1' Howco guide shoe 1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs  Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.	and set @ 358' RKB.	Centralizers on first	and third collars. $C\epsilon$	emented with 375 sxs Clas
1' Howco guide shoe  1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on 1st, 3rd, and 5th joints. Cemented with 350 sxs  Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.  The production Engr.  PATE Production Engr.  DATE 11-20-74				
1325' 9 5/8" 36# S-80 ST&C (36 jts)  2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs  Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.  Production Engr. DATE NOV CAPPROVED BY TITLE Production Engr.			o 4168'. Ran 9 5/8'' ca	asing as follows:
2855' 9 5/8" 36# K-55 ST&C (60 jts)  4181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs  Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNED TITLE Production Engr.  DATE NOV 7				
A181' set @ 4168'. Cemtralizer on lst, 3rd, and 5th joints. Cemented with 350 sxs Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18. I hereby certify that the information above is true and complete to the beat of my knowledge and belief.  SIGNED TITLE Production Engr. DATE 11-20-74				
Class H. Plug down @ 7:00 PM 11-17-74. WOC 24 hrs. Calculated top of cement is 3160'. Tested casing to 1000 psi - 30 min, OK.  18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNED Production Engr. DATE 11-20-74			3rd. and 5th joints.	Cemented with 350 sxs
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNED Milia Production Engr.  DATE 11-20-74	Class H. Plug down	@ 7:00 PM 11-17-74.	WOC 24 hrs. Calcul	lated top of cement is
APPROVED BY				
APPROVED BY DATE	18. I hereby certify that the information a	above is true and complete to the be	st of my knowledge and belief.	
APPROVED BY DATE DATE	SIGNED Michael 19	Vicieties TITLE	Production Engr.	DATE 11-20-74
APPROVED BY				NOV ?
	<del></del>	nts """		DATE

The Control of Control

CIL CRAN TRACTING COMM.