

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>11,355</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>11,522</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>3250</u>	T. Miss <u>11,884</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian <u>13,027</u>	T. Menefee _____	T. Madison _____
T. Queen <u>4163</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4932</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>6376</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>8052</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard <u>8200</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>8600</u>	T. Bone Springs <u>8716</u>	T. Wingate _____	T. _____
T. Wolfcamp <u>9098</u>	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1900	1900	Surface sands & salt				
1900	3102	1202	Salt & anhydrite				
3102	3250	148	Anhydrite & salt - Tansil				
3250	4163	913	Yates				
4163	4932	769	Lime & anhydrite - Queen				
4932	6376	1444	Anhydrite & dolomite - San Andres				
6376	8052	1676	Lime, sand & shale - Glorieta				
8052	8200	148	Dolomite & lime - Tubb				
8200	8326	126	Dolomite - Drinkard "A"				
8326	8600	274	Dolomite-Drinkard "B"				
8600	8716	116	Shale - Abo				
8716	8796	80	Sand & shale - 3rd Bone Springs				
8796	9098	302	Lime & dolomite - Abo				
9098	11355	2257	Dolomite & shale - Wolfcamp				
11355	11522	167	Lime & shale - Strawn				
11522	11884	362	Lime & sand - Atoka				
11884	12150	266	Shale, lime & dolomite - Chester				
12150	12917	767	Lime & shale - Osage				
12917	13027	110	Lime & dolomite - Woodford				
13027	12250	223	Shale & lime - Devonian				