

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-55

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LC 272

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Junked and abandoned	7. Unit Agreement Name
2. Name of Operator Franklin, Aston & Fair, Inc.	8. Farm or Lease Name Aztec State
3. Address of Operator P.O. Box 1090 Roswell, New Mexico	9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 17S RANGE 32E NMPM.	10. Field and Pool, or Wildcat Corbin Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3966.8 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER Junk & abandon ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was drilled to a depth of 2975'. The 13-3/8" surface casing was set 320' with cement circulated to surface. The 8-5/8" casing was set at 2975' and collapsed while being set with 1200 sacks Halliburton lite cement followed by 150 sacks of Class H 2% CaCl. The collapsed casing was pulled at depth of 720'. Pursuant to telephone conversation with Mr. Ramey, we plan to plug and abandon as follows:

200' plug from 850' to 650' across top of collapsed casing  
100' plug in and out of the 13-3/8 from 280' to 380'.  
10 sack plug and marker will be placed at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Grant M. Smith

TITLE Geologist

DATE 1-6-75

Orig. Signed by  
Joe P. Ramey

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: