

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>11,314</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>11,427</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>3133</u>	T. Miss <u>11,993</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>3992</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4760</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>6286</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>7503</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>8204</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>9561</u>	T. Rustler <u>1935</u>	T. Chinle _____	T. _____
T. Penn. _____	T. Tansil <u>3004</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. 3 Bros. <u>10,308</u>	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1935	1935	Surface sands and red bed				
1935	3133	1198	Anhydrite & Salt				
3133	3992	859	Anhydrite & Gyp				
3992	4760	768	Anhydrite & lime				
4760	6286	1526	Dolomite & Anhydrite				
6286	7503	1217	Dolomite & Shale				
7503	8204	701	Lime & Shale				
8204	9561	1357	Lime, Anhydrite & Shale				
9561	10308	747	Lime & Shale				
10308	11314	1006	Lime & Shale - Wolfcamp				
11314	11427	113	Lime & Shale - Strawn				
11427	11993	566	Lime, Sand, & Shale - Atoka				
11993	12050	57	Lime & Shale - Miss.				

