

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Hanson Oil Corporation		8. Farm or Lease Name Caldonia
3. Address of Operator P.O. Box 1515 Roswell, New Mexico 88201		9. Well No. #1
4. Location of Well UNIT LETTER <u>N</u> , <u>1980</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>11</u> TOWNSHIP <u>16-S</u> RANGE <u>34-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Eidson Penn-Undes
15. Elevation (Show whether DF, RT, GR, etc.) 4082.9 G.L.		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-19-75 T.D. 10,950', Run 250 jts. 4½" 11.60# N-80 csg. to 10,921' w/ D.V. tool set @ 5797', cemented first stage w/ 1000 gal. mud flush & 250 sx. 50/50 pozmix Cl. H, w/ 7# salt per sx., .4# flocler per sx., 3/4 of 1% CFR-2, plugged down @ 7:45 p.m., closed D.V. tool, circ. hole for 6 hrs., cemented second stage w/ 1000 gal mud flush & 350 sx. 50/50 pozmix Cl."C" w/ 8# salt per sx., ½ of 1% CFR-2, .4# flocler per sx., plugged down @ 2:35 a.m. 5-20-75. Tested to 1500 P.S.I. for 30 minutes, Held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray W. [Signature] TITLE Vice President-Prod. DATE 5-21-75

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: