

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Hanson Oil Corporation	8. Farm or Lease Name Caldonia
3. Address of Operator P.O. Box 1515 Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER N 1980 FEET FROM THE West LINE AND 660 FEET FROM THE South LINE, SECTION 11 TOWNSHIP 16-S RANGE 34-E N.M.P.M.	10. Field and Pool, or Wildcat Eidson Penn-Undes
15. Elevation (Show whether DF, RT, GR, etc.) 4082.9 G.L.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-8-75 Spudded well @ 4:00 P.M.

4-9-75 T.D. 369', ran 369' 12 3/4" surface pipe, cemented w/ 400 sx. Cl."C" w/ 2% cal. chl., (cement circ.) W.O.C. 18 hrs. tested cement to 500 P.S.I., (held okay)

4-23-75 T.D. 4574', run 62 jts. of 52#, 8 5/8" csg. (2501.97) and 52 jts. of 24#, 8 5/8" csg. (2098.61), set @ 4570', cemented w/ 625 sx. Halliburton lite w/ 10# salt per sx. and 100 sx. Cl."C" w/ 2% cal. chl. W.O.C. 18 hrs., tested cement to 800 P.S.I. ( held okay ).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Kay M. Miller TITLE Vice President - Prod. DATE 4-21-75

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: