

BOTTOM HOLE PRESSURE AND TIME DATA

INSTRUMENT NO.: T-136 CAPACITY(P.S.I.): 7000 DEPTH: 10589 FT.
 PORT OPENING: OUTSIDE BOTTOM HOLE TEMP.: 160 PAGE 1 OF 2

DESCRIPTION	LABELED POINTS	PRESSURE (P.S.I.)	GIVEN TIME	COMPUTED TIME
INITIAL HYDROSTATIC MUD	1	4851.4		
INITIAL FLOW(1)	2	251.9		
INITIAL FLOW(2)	3	326.3	15	16
INITIAL SHUT-IN	4	2233.0	60	61
FINAL FLOW(1)	5	522.9		
FINAL FLOW(2)	7	195.8	120	119
FINAL SHUT-IN	8	2197.9	360	360
FINAL HYDROSTATIC MUD	9	4831.8		

CHARTS INDICATE PERFORATED ANCHOR
 PLUGGING DURING TEST.

INCREMENTAL READINGS

LABEL POINT	DELTA TIME	PRESSURE (P.S.I.)	T + DT/DT	LOG	PW - PF (P.S.I.)	COMMENTS
1		4851.4				HYDROSTATIC MUD
2	0	251.9				INITIAL FLOW(1)
3	16	326.3				INITIAL FLOW(2)
3	0	326.3				STARTED SHUT-IN
	5	946.9	4.200	0.623	620.6	
	10	1427.1	2.600	0.415	1100.7	
	15	1818.8	2.067	0.315	1492.5	
	20	2081.3	1.800	0.255	1755.0	
	25	2178.2	1.640	0.215	1851.9	
	30	2202.1	1.533	0.186	1875.7	
	35	2211.9	1.457	0.164	1885.6	
	40	2217.5	1.400	0.146	1891.2	
	45	2223.1	1.356	0.132	1896.8	
	50	2227.4	1.320	0.121	1901.0	
	55	2230.2	1.291	0.111	1903.8	
	60	2231.6	1.267	0.103	1905.2	
4	61	2233.0	1.262	0.101	1906.6	INITIAL SHUT-IN
5	0	522.9				FINAL FLOW(1)
6	83	573.4				FLOW POINT
7	119	195.8				FINAL FLOW(2)
7	0	195.8				STARTED SHUT-IN
	5	611.4	28.000	1.447	415.6	
	10	955.3	14.500	1.161	759.6	
	15	1299.3	10.000	1.000	1103.5	
	20	1605.4	7.750	0.889	1409.6	
	25	1849.7	6.400	0.806	1653.9	
	30	1995.7	5.500	0.740	1799.9	
	35	2050.5	4.857	0.686	1854.7	
	40	2072.9	4.375	0.641	1877.1	
	45	2085.6	4.000	0.602	1889.8	
	50	2094.0	3.700	0.568	1898.2	
	55	2101.0	3.455	0.538	1905.2	