

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-2229
7. Unit Agreement Name
8. Farm or Lease Name Phillips E State
9. Well No. 20
10. Field and Pool, or Wildcat Maljamar Gb/San Andres
12. County LEA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Oil Well ☒ Gas Well ☐ Other ☐

1. Name of Operator  
Phillips Petroleum Company

2. Address of Operator  
Room 711, Phillips Bldg., Odessa, Texas 79761

3. Location of Well  
UNIT LETTER H 1980 FEET FROM THE North 660 LINE AND FEET FROM  
THE East 15 LINE, SECTION 17S 33E TOWNSHIP 33E RANGE 15 NADPH.

15. Elevation (Show whether DF, RT, GR, etc.)  
4161' DF, 4152' GR

**Check Appropriate Box To Indicate Nature of Notice, Report or Other Data**

<b>NOTICE OF INTENTION TO:</b>		<b>SUBSEQUENT REPORT OF:</b>	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Prep to complete

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1102.

Reached TD of 4566' in 7-7/8" hole at 6:45 AM, 3-30-75. Dresser Atlas ran compensated density, GR, and caliper logs. Set 4566' of 5-1/2" OD 17# N-80 casing at 4566'. Howco cemented w/125 sx Class H cmt w/40% DD followed by 150 sx Class H w/8# salt per sx. Plug to 4540' w/6 bbls 10% acetic acid and 99 BW. Bumped plug w/2000# at 4 AM, 3-31-75. WOC 2 hours, ran temp. survey, TOC at 2600'.

Prep to perf. and complete.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W. J. Mueller TITLE Senior Reservoir Engineer DATE 4-2-75

APPROVED BY John Runyan TITLE Geologist DATE 3-16-75

CONDITIONS OF APPROVAL, IF ANY: