

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator C & K Petroleum, Inc.		8. Farm or Lease Name Shipp "34"
3. Address of Operator 607 Midland National Bank Bldg., Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>K</u> 1980 FEET FROM THE <u>South</u> LINE AND 1980 FEET FROM THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>16-S</u> RANGE <u>37-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Shipp (Drinkard)
15. Elevation (Show whether DF, RT, GR, etc.) 3774.6		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	
ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 9:00 a.m. April 20, 1975
Drilled 17-1/2" hole 353, set 13-3/8" casing at 353'. Cemented with 350 sx. Class "C" Cement. Cement circulated to surface. WOC 18 hrs. Tested 1000# 30 min. Held OK. Drilled 11" hole to 4235'. Set 8-5/8" casing at 4230'. Cemented with 450 sx. Halliburton Lite and 150 sx Class "C" cement, plug down at 10:00 a.m. 4-30-75. WOC 18 hrs. Tested with 1800# 30 min. Held OK. Drilled 7-7/8" hole to 8805 TD. set 4-1/2" casing @ 8805'. Cemented with 740 sx Class "C". Plug down at 8:30 a.m. 5/20/75. WOC excess 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Administrative Supervisor DATE 5-22-75

Orig. Signed by

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: