

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy <u>2110</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>3220</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>4128</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4870</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>6308</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock <u>6420</u>	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>7950</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard <u>8126</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>8474</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. Tansill <u>3090</u>	T. Chinle _____	T. _____
T. Penn. _____	T. Drinkard "B" <u>8212</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2415	2415	Surface sands, red bed, & salt				
2415	3220	805	Salt and anhydrite				
3220	4128	908	Anhydrite				
4128	4870	742	Anhydrite				
4870	6308	1438	Dolomite & anhydrite				
6308	6420	112	Dolomite, lime & anhydrite				
6420	7950	1530	Lime & anhydrite				
7950	8126	176	Lime & shale				
8126	8474	348	Dolomite, & shale - Drinkard				
8474	8575	101	Shale				