

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6966
7. Unit Agreement Name
8. Farm or Lease Name Read State
9. Well No. 1
10. Field and Pool, or Wildcat Townsend Wolfcamp
12. County Lea

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-

2. Name of Operator  
Tri-Service Drilling Company

3. Address of Operator  
P. O. Drawer 70 - Midland, Texas 79701

4. Location of Well  
UNIT LETTER G 1980 FEET FROM THE East LINE AND 2246 FEET FROM  
THE North LINE, SECTION 4 TOWNSHIP 16-S RANGE 35-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)  
4027' G.R.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:  
REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-6-76 Plug #1: C.I.B.P. w/ 35' cmt. at 11,180'  
Plug #2: C.I.B.P. w/ 35' cmt. at 10,100'. Cut 5-1/2" casing. Recovered 176 jts. (7449.38') loaded hole with brine water & gel.  
Plug #3: 35 sks. plug at 7450, tag top of plug at 7355'.  
Plug #4: 35 sks. cmt. at 6128'. Top of plug at 6028'. Loaded hole with brine & bel.  
Plug #5: 45 sks. cmt. at 4575', top of plug at 4475. Loaded hole w/ brine and gel. Cut 8-5/8" casing at 1385'. Recovered 33 jts. (1385.37') loaded hole with brine and gel.  
Plug #6: 50 sks. cmt. 1433'. Top of plug at 1335'.  
Plug #7: 80 sks. cmt. at 500'. top of plug 379'.  
Plug #8: 10 sks. at surface with dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. V. Allen TITLE Prod. Supt.

DATE 10-15-76

APPROVED BY John W. Runyan TITLE Geologist

DATE JUN 28 1977

CONDITIONS OF APPROVAL, IF ANY: