DISTRIBUTION		Form C-103 Supersedes Old C-102 and C-103
	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 14-65
J.S.G.S.		5a. Indicate Type of Lease State X Fee
AND OFFICE		5, State Oil & Gas Lease No.
PERATOR		
SUNDRY NOTIC (DO NOT USE THIS FORM FOR PROPOSALS TO USE "APPLICATION FOR PER	CES AND REPORTS ON WELLS DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. RMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
	- Dry	
Name of Operator		8. Farm or Lease Name
John H. Hill		Amoco State
Address of Operator	75206	
	350 N. Central Expressway Dallas, T	
Location of Well		Kemnitz West, Lower
-	_ FEET FROM THE EINE FROM THE	TT FROM
THE east LINE, SECTION 3	B6 TOWNSHIP 16 S RANGE 32 E	_ ммрм. Д
	15. Elevation (Show whether DF, RT, CR, etc.)	12. County
	4249 Gr. 4261 KB	Lea Allllll
Check Approprise NOTICE OF INTENTIC	iate Box To Indicate Nature of Notice, Report ON TO:	OF Other Data QUENT REPORT OF:
	PLUG AND ABANDON X REMEDIAL WORK	ALTERING CASING
PERFORM REMEDIAL WORK	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS CASING TEST AND CEMENT JOB	
PULL OR ALTER CASING	OTHER Completion	LattemptX
0 YUE 8		
OTHER	(Clearly state all pertinent details, and give pertinent dates, i	ncluding estimated date of starting any proposed
work) SEE RULE 1103.	& Bond logs, top of cement 9410'. Tes Nolfcamp 10,628'-10,742', swabbed w	sted casing to 3500#.
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150"	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 580' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 580' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 580' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150'	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150' at surface. Plugs will be d	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 880' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150' at surface. Plugs will be d	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 80' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150' at surface. Plugs will be d	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 80' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in s pulled, and 30' plug
Set cast iron bridge plug @ swabbed, no show. Set cas Propose to shoot 4 1/2" cas casing from stub to fill 150' Abo, 50 sk plug 5830' to 56 and out 8 5/8" casing, 150' at surface. Plugs will be d	st iron bridge plug @ 9550', dumped 35 sing off @ approx. 9300', pump 50 sk o ', pump 50 sk plug down 4 1/2" from 7 80' @ base of San Andres, 45 sk plug ' plug at top of 8 5/8" if any 8 5/8" is lisplaced w/9.2# mud.	5' cement on top. cement plug down 4 1/2" '910' to 7760' at top of from 4485' to 4335' in a pulled, and 30' plug

REDEIVED OIL COMPONIATES & COMM.