

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-55

<p>SUNDRY NOTICES AND REPORT ON WELLS</p> <p>DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.</p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p> <p>5. State Oil & Gas Lease No. N/A</p>
<p>1. Name of Operator R. L. Burns Corp.</p>		<p>7. Unit Agreement Name -----</p>
<p>2. Address of Operator 3990 First National Bank Building, Dallas, Texas 75202</p>		<p>8. Farmer or Lease Name Bullis '20'</p>
<p>3. Location of Well UNIT LETTER <u>P</u> , <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>20</u> TOWNSHIP <u>16S</u> RANGE <u>38E</u> N.M.P.M.</p>		<p>9. Well No. 1</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 3725.2' GR.</p>		<p>10. Field and Pool, or Wildcat Garrett (Drinkard)</p>
<p>12. County Lea</p>		

<p>Check Appropriate Box To Indicate Nature of Notice, Report or Other Data</p>	
<p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/></p> <p>TEMPORARILY ABANDON <input type="checkbox"/></p> <p>PULL OR ALTER CASING <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p>	<p>SUBSEQUENT REPORT OF:</p> <p>PLUG AND ABANDON <input type="checkbox"/></p> <p>CHANGE PLANS <input type="checkbox"/></p> <p>REMEDIAL WORK <input type="checkbox"/></p> <p>COMMENCE DRILLING OPNS. <input type="checkbox"/></p> <p>CASING TEST AND CEMENT JOB <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p> <p>ALTERING CASING <input type="checkbox"/></p> <p>PLUG AND ABANDONMENT <input checked="" type="checkbox"/></p>
<p>7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of work) SEE RULE 1103.</p>	

1. Set cast iron BP @ 7930'. capped with 35' cement. Loaded hole with 10# salt gel.
2. Set cast iron BP @ 7500', capped with 35' cement.
3. Cut 5-1/2" casing at 6203' and pulled.
4. Spotted 70 sx Class "C" cement plug @ 6245-6500'. Tagged @ 6055'.
5. Spotted 200 sx Class "C" cement plug @ 5080-4740'. Waited on cement 4 hrs, tagged plug @ 4740'.
6. Spotted 35 sx Class "C" cement plug @ 2100-2000'.
7. Cut 8-5/8" casing at 742' and pulled.
8. Spotted 300 sx Class "C" cement plug @ 742-250'. Waited on cement, tagged at 347'.
9. Spotted 30 sx Class "C" cement plug @ 0-60'.
10. Welded plate on 13-3/8" casing, installed dry hole marker.

8. I hereby certify that the information above is true and complete to the best of my knowledge.

SIGNED Walter H. Hight TITLE Production Engineer date: June 10, 1977

PROVED BY Nathan E. Olegg TITLE OIL & GAS INSPECTOR APR 14 1978

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 13 1977

OIL CONSERVATION COMM.
ROBES, R. M.