

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon	10532
T. Salt	T. Strawn LS	12046
T. Salt	T. Atoka	12239
T. Yates 2580	T. Miss Austin Cycle	13207
T. 7 Rivers	T. Devonian	
T. Queen 3402	T. Silurian	
T. Grayburg	T. Montoya	
T. San Andres 4151	T. Simpson	
T. Glorieta 5747	T. McKee	
T. Paddock	T. Ellenburger	
T. Blinbry	T. Gr. Wash	
T. Tubb 7030	T. Delaware Sand	
T. Drinkard	T. Bone Springs	
T. Abo 7758	T. Three Brothers	-9890
T. Wolfcamp 9200	T. Bursum	-10095
T. Penn	T. Atoka Sh	-12400
T. Cisco (Bough C) 10163	T. Morrow LS	-12718
T. Morrow Clastic		-12916

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
			WELL DEEPENED FROM 10500 TO 13320				
			REFER TO ORIGINAL COMPLETION .				
10500	10890	390	LS, Sh				
10890	11070	180	LS				
11070	11230	160	LS, Sh				
11230	11290	60	LS, DoLo				
11290	11480	190	LS, Sh				
11480	11570	90	LS, Sh, SS				
11570	12480	910	LS, Sh				
12480	12680	200	LS, SS, Sh				
12680	13320	640	LS, Sh				