

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE APPLICATION FOR PERMIT TO DRILL OR TO RE-OPEN FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No. LG-3043
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-		7. Unit Agreement Name N.E. Anderson Ranch Unit
2. Name of Operator Marathon Oil Company		8. Form or Lease Name N.E. Anderson Ranch Unit
3. Address of Operator P. O. Box 2409, Hobbs, New Mexico 88240		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u>, <u>2030</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>14</u> TOWNSHIP <u>15S</u> RANGE <u>32E</u> N.M.P.M.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, CR, etc.) G.L. 4266'		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set 400' cement plug through Bursum and top of Cisco at 10,000-10,400' with 134 sacks Class "H" containing 5/10% CFR-2.
- Set 200' cement plug in top of Wolfcamp at 9100-300' with 67 sacks Class "H" containing 5/10% CFR-2.
- Set 200' cement plug in top of Abo at 7700-900' with 67 sacks Class "H" neat.
- Set 200' cement plug in top of Glorieta at 5600-800' with 67 sacks Class "H" neat.
- Set 200' cement plug at base of 9 5/8" intermediate casing at 4100-300' with 100 sacks Class "H".
- Set 200' cement plug inside 9 5/8" casing opposite salt section at 1500-1700' with 75 sacks Class "H" neat.
- Set 200' cement plug at top of 9 5/8" casing with 75 sacks Class "H". Hole will be loaded with 9# mud above and below plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Robert J. Quenschel</u> Dist. 1, Supv.	TITLE <u>Petroleum Engineer</u>	DATE <u>September 14, 1976</u> SEP 17 1976
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

SEP 14 1976

OIL CONSERVATION COMM.
HOBBS, N. M.