

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-1587

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator H. L. BROWN, JR. 3. Address of Operator P. O. Box 2237, Midland, Texas 79701 4. Location of Well UNIT LETTER <u>J</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>15-S</u> RANGE <u>32-E</u> NMPM.	7. Unit Agreement Name 8. Farm or Lease Name State UTP 9. Well No. 1 10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4310 GR	12. County Lea

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled a 11" hole under 12 3/4" OD csg at 500' to 4112'. Ran 100 joints of 8 5/8" OD K-55 32# & 24# csg to 4112'. Cemented w/1600 sx Dowell Lite w/1/4#/sx D-29, 10#/sx NaCl, followed by 250 sx Class C w/2% CaCl<sub>2</sub>. Plug Down at 1:30 PM, 9-30-76. Did not circ. WOC 15 1/4 hrs. Ran temp survey, found top of cement at 290' (inside 12 3/4" OD csg at 500'). Cut off 8 5/8" csg. Installed BOP. Pressure tested csg to 1000 psi for 30". Held with no loss pressure. WOC total 18 hrs. Drilled out under 8 5/8" csg w/ 7 7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. L. McGill J. L. McGill TITLE Production & Drilling Manager DATE October 1, 1976

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE Oct 6 1976

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

1973

1973