

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-2229

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Phillips Petroleum Company	Phillips-E State
3. Address of Operator	9. Well No.
Room 806, Phillips Bldg., Odessa, TX 79761	28
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER J, 1980 FEET FROM THE south LINE AND 1980 FEET FROM THE east LINE, SECTION 14 TOWNSHIP 17-S RANGE 33-E NMPM.	Maljamar Gb/San Andres
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4132' Gr. 4139' RKB	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drld to 4800', reached at 12:45 PM, 3-31-77. Cond hole, COOH. Dresser Atlas ran Gr. Caliper and densilog. Set 115 jts (4800') 4-1/2" OD11.6# N-80 csg at 4800'. BJ cemented w/1000 sx LW cmt w/12# salt, 10% DD, 1/4# Flocele and 3# Gilsonite per sx, followed by 150 sx Class H cmt w/8# salt/sx. Plug to 4759' w/6 bbls 10% acetic acid and 68 BW. Released rig.

Prep to perf & complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Advisor DATE 4-5-77

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 1 1977

Ch. 3, Sec. 1, Item 10
HDSB, R. 1.