

INSTRUCTIONS

This form is to be filed with the appropriate permit. It must be submitted to the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It should contain a complete log of all electrical and radioactivity logs run on the well and a summary of all special tests, including aquifer, mechanical, and other tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 1 through 14 shall be reported for each zone. The form is to be filed in quintuplicate except in states where six copies are required. See Rule 11.3.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>2140</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>11,333</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>11,915</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>3244</u>	T. Miss <u>12,560</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian <u>14,080</u>	T. Menefee _____	T. Madison _____
T. Queen <u>4086</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4981</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzite _____
T. Glorieta <u>6580</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb <u>7705</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>8427</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>9400</u>	T. _____	T. Chinle _____	T. _____
T. Penn. <u>10,576</u>	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from <u>10,600'</u> to <u>10,630'</u>	No. 4, from <u>13,720'</u> to <u>13,765'</u>
No. 2, from <u>10,630'</u> to <u>10,677'</u>	No. 5, from _____ to _____
No. 3, from <u>11,024'</u> to <u>11,050'</u>	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from <u>drld. w/rotary tools</u> to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet
No. 4, from _____ to _____ feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	370	370'	Surface soil & redbeds				
370	1530	1160'	Redbeds				
1530	2185	655'	Anhydrite				
2185	4115	1930'	Salt & Anhy.				
4115	5013	998'	Anhy. & Dol.				
5013	8259	3246'	Dol. & Li.				
8259	9540	1281'	Dol. & Shale				
9540	11065	1525'	Li. & Sh. & Dol.				
11065	12000	935'	Li. & Sh.				
12000	12440	440'	Sh.				
12440	14107	1667'	Sh. & Li.				

FEB 8 1978
CAL. CONSUL. FROM U.S.A.
HOBBS, N. M.