

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL IF YOU C-101 FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☐ Fee ☒
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-		5. State Oil & Gas Lease No.
2. Name of Operator G. W. Brock, Inc.		7. Unit Agreement Name
3. Address of Operator 901 Gihls Tower West, Midland, Texas 79701		8. Form of Lease Name Mauldin-Heirs
4. Location of Well UNIT LETTER <u>G</u> , <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>27</u> TOWNSHIP <u>15-S</u> RANGE <u>37-E</u> N.M.P.M.		9. Well No. <u>1</u>
10. Field and Pool, or Wildcat Wildcat		
11. Elevation (Show whether DF, RT, GR, etc.) 3802 K.B.		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐				
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐				
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐					
		OTHER ☐					

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Estimated starting Date 8-12-77

1. Set 20sx cement plug from 10,600-10,500'.
2. Cut off & pull 5½" casing at free point.
3. Set 40sx cement plug in & out the top of 5½" casing.
4. If 5½" is pulled below 8500', then set a 40sx cement plug from 8477' to 8377'.
5. Set 40sx cement plug from 7755' to 7655'.
6. Set 40sx cement plug from 6630' to 6530'.
7. Set 40sx cement plug from 5063' to 4963' (in & out the base of 9 5/8" csg.)
8. Set 50sx cement plug from 2000' to 1900' (across top of salt section).
9. Set 10sx cement plug at surface. Cut of head & install marker.

9.5# weight mud will be placed between all plugs.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. P. Roney TITLE Petroleum Engineer DATE 8-5-77
 Original Signed by Jerry Sexton
 District 1 Supv. TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

AUG 10 1977

RECEIVED

JUL 16 1977

OIL CONSERVATION COMM.
HOBBS, N. M.