

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	high density wet process porcelain pin insulator		463		
D	5/8" x 5" forged steel pin w/sq. washer, nut, & locknut	881			
E	5/8" x 12" machine bolt w/ nut (or length req'd)	8812			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	6813			
G	5/8" NF locknut	3512			
H	wood chassidom brace 1 5/8" x 2 5/8" x 5 5/8"	508754		Gray Bar #217	X
J	1/2" x 4" EZ Patter Drive log screw	8634 1/2			
K	3/8" x 4 1/2" Carriage Bolt w/ Nut	3510			
L	3/8" NF locknut				
M	Preformed Aluminum Alloy Armor Rods, size req'd				
N	tie wire #6 strong alum. alloy				
O					
P	46' class 5 creosoted pine pole				
R	Aluminum double tab Squeeze on Connector for ACSR, Aluminum, or Copper-size req'd			KEARNEY SERIES "81"	X
S	6" Suspension Insulator	66200			
T	5/8" Standard Oval Eye Nut	6502			
U	Primary Feed End Clamp		14050		
V	5/8" x 18" (or length req'd) Double Arming Bolt w/4 sq. nuts	8868			
X	guying detail - see detg No. ES-10 for specs.				
Y	Hot Line Clamp	51520AGP			
Z	Squeeze on basket, size required			KEARNEY	X

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO HOBBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:		JOB: ES-1	
SCALE: NONE		DRAWING NO: SHEET 1 OF 3	
PRODUCTION DEPT.		HOBBS DIVISION	
ELEC SPECS			

CONOCO
PEARL B NO.5

RECEIVED

MAY 17 1977

OIL CONSERVATION COMM.
HOBBS, N. M.